

# ACCHECK: Check Address Converter Against Data Storage

```
ADAACK ACCHECK [FILE={ file | file - file | all-files }]
                [ISN={ isn - isn | all-isn }]
                [NOUSERABEND]
```

This chapter covers the following topics:

- Optional Parameters
  - Examples
- 

## Optional Parameters

### FILE: Files to be Checked

The file, single range of files, or all files to be checked. By default, all files in the database are checked.

### ISN: ISN Range to be Checked

A range of ISNs or all ISNs to be checked. By default, the entire range MINISN through TOPISN is checked.

### NOUSERABEND: Termination Without ABEND

When an error is encountered while the function is running, the utility prints an error message and terminates with user ABEND 34 (with a dump) or user ABEND 35 (without a dump).

If NOUSERABEND is specified, the utility will *not* ABEND after printing the error message. Instead, the message "utility TERMINATED DUE TO ERROR CONDITION" is displayed and the utility terminates with condition code 20.

## Examples

### Example 1:

```
ADAACK ACCHECK
```

Check all files in the database.

### Example 2:

```
ADAACK ACCHECK FILE=12, ISN=1-8000
```

Check ISNs 1 through 8000 for file 12.

**Example 3:**

```
ADAACK ACCHECK FILE=8-10
```

Check all ISNs in files 8 through 10.